



IECEX Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.: **IECEX BAS 18.0082X** Page 1 of 5 Certificate history:
Status: **Current** Issue No: 3 Issue 2 (2020-01-16)
Date of Issue: 2020-06-11 Issue 1 (2019-03-22)
Issue 0 (2018-11-09)
Applicant: **Hansford Sensors Limited**
Artisan
Hillbottom Road
Sands Industrial Estate
Bucks
HP12 4HJ
United Kingdom
Equipment: **HS-150I & HS170I Series Accelerometers**
Optional accessory:
Type of Protection: **Intrinsic Safety**
Marking: See Certificate Schedule for Marking Details

Approved for issue on behalf of the IECEx
Certification Body:

R S Sinclair

Position:

Technical Manager

Signature:
(for printed version)

Date:

11-6-2020

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting www.iecex.com or use of this QR Code.



Certificate issued by:

SGS Baseefa Limited
Rockhead Business Park
Staden Lane
Buxton, Derbyshire, SK17 9RZ
United Kingdom





IECEX Certificate of Conformity

Certificate No.: **IECEX BAS 18.0082X**

Page 2 of 5

Date of issue: 2020-06-11

Issue No: 3

Manufacturer: **Hansford Sensors Limited.**
Artisan
Hillbottom Road
Sands Industrial Estate
Bucks
HP12 4HJ
United Kingdom

Additional
manufacturing
locations:

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended

STANDARDS :

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

IEC 60079-0:2017 Explosive atmospheres - Part 0: Equipment - General requirements
Edition:7.0

IEC 60079-11:2011 Explosive atmospheres - Part 11: Equipment protection by intrinsic safety "i"
Edition:6.0

This Certificate **does not** indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Reports:

[GB/BAS/ExTR18.0244/00](#)
[GB/BAS/ExTR19.0347/01](#)

[GB/BAS/ExTR19.0059/00](#)

[GB/BAS/ExTR19.0347/00](#)

Quality Assessment Report:

[GB/BAS/QAR07.0040/08](#)



IECEX Certificate of Conformity

Certificate No.: **IECEX BAS 18.0082X**

Page 3 of 5

Date of issue: 2020-06-11

Issue No: 3

EQUIPMENT:

Equipment and systems covered by this Certificate are as follows:

The HS-150i and HS-170i Series Accelerometers are designed to measure acceleration or vibration by converting the signal generated by the compression of a Piezo electric crystal by a given seismic mass and outputting a broadband ac signal to the monitoring equipment.

The accelerometer comprises of a piezo electric crystal connected to a signal conditioning board, all contained within a fully welded steel enclosure.

HS-150xT versions include a temperature transmitter.

HS-173 is a tri-axial accelerometer comprising three individual circuits with common 0V line, sharing a single set of parameters.

Electrical connections are made via a connector or integral cable. The equipment carries the following markings:

SPECIFIC CONDITIONS OF USE: YES as shown below:

1. Where equipment is supplied with an attached cable, this must be terminated in an enclosure providing at least degree of protection IP20.

2. The equipment is marked with reduced certification markings. Refer to the Certificate Schedule for the full certification markings & applicable temperature classification and associated ambient temperature range.



IECEX Certificate of Conformity

Certificate No.: **IECEX BAS 18.0082X**

Page 4 of 5

Date of issue: 2020-06-11

Issue No: 3

Equipment (continued):

Uni-axial accelerometers with integral cable

Ex ia IIC T6 Ga $-55^{\circ}\text{C} \leq \text{Ta} \leq +57^{\circ}\text{C}$
Ex ia IIC T4 Ga $-55^{\circ}\text{C} \leq \text{Ta} \leq +103^{\circ}\text{C}$

Ex ia IIIC T₂₀₀110°C Da $-55^{\circ}\text{C} \leq \text{Ta} \leq +57^{\circ}\text{C}$
Ex ia IIIC T₂₀₀135°C Da $-55^{\circ}\text{C} \leq \text{Ta} \leq +70^{\circ}\text{C}$
Ex ia IIIC T₂₀₀145°C Da $-55^{\circ}\text{C} \leq \text{Ta} \leq +92^{\circ}\text{C}$

Ex ia I Ma $-55^{\circ}\text{C} \leq \text{Ta} \leq +103^{\circ}\text{C}$

Uni-axial accelerometers with connectors

Ex ia IIC T6 Ga $-55^{\circ}\text{C} \leq \text{Ta} \leq +57^{\circ}\text{C}$
Ex ia IIC T4 Ga $-55^{\circ}\text{C} \leq \text{Ta} \leq +103^{\circ}\text{C}$

Ex ia IIIC T₂₀₀135°C Da $-55^{\circ}\text{C} \leq \text{Ta} \leq +70^{\circ}\text{C}$

Ex ia IIIB T₂₀₀110°C Da $-55^{\circ}\text{C} \leq \text{Ta} \leq +57^{\circ}\text{C}$
Ex ia IIIB T₂₀₀145°C Da $-55^{\circ}\text{C} \leq \text{Ta} \leq +92^{\circ}\text{C}$

Ex ia I Ma $-55^{\circ}\text{C} \leq \text{Ta} \leq +103^{\circ}\text{C}$

Tri-axial Accelerometers with integral cable.

Ex ia IIC T6 Ga $-55^{\circ}\text{C} \leq \text{Ta} \leq +69^{\circ}\text{C}$
Ex ia IIC T4 Ga $-55^{\circ}\text{C} \leq \text{Ta} \leq +104^{\circ}\text{C}$

Ex ia IIIC T₂₀₀102°C Da $-55^{\circ}\text{C} \leq \text{Ta} \leq +69^{\circ}\text{C}$
Ex ia IIIC T₂₀₀131°C Da $-55^{\circ}\text{C} \leq \text{Ta} \leq +98^{\circ}\text{C}$

Ex ia I Ma $-55^{\circ}\text{C} \leq \text{Ta} \leq +104^{\circ}\text{C}$

Triaxial accelerometers with connectors.

Ex ia IIC T6 Ga $-55^{\circ}\text{C} \leq \text{Ta} \leq +69^{\circ}\text{C}$
Ex ia IIC T4 Ga $-55^{\circ}\text{C} \leq \text{Ta} \leq +104^{\circ}\text{C}$

Ex ia IIIC T₂₀₀135°C Da $-55^{\circ}\text{C} \leq \text{Ta} \leq +70^{\circ}\text{C}$

Ex ia IIIB T₂₀₀102°C Da $-55^{\circ}\text{C} \leq \text{Ta} \leq +69^{\circ}\text{C}$
Ex ia IIIB T₂₀₀131°C Da $-55^{\circ}\text{C} \leq \text{Ta} \leq +98^{\circ}\text{C}$

Ex ia I Ma $-55^{\circ}\text{C} \leq \text{Ta} \leq +104^{\circ}\text{C}$

See Certificate Annex for terminal parameters.



IECEX Certificate of Conformity

Certificate No.: **IECEX BAS 18.0082X**

Page 5 of 5

Date of issue: 2020-06-11

Issue No: 3

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above)
Variation 3.1

Correction to Annex only

Annex:

[IECEX BAS 18.0082X Annex 1.pdf](#)

The HS-150i and HS-170i Series Accelerometers

The equipment has the following terminal parameters:

Uni-axial accelerometer.

Connector Only	
U _i	= 28 V
I _i	= 93 mA
P _i	= 0.65 W
C _i	= 1.2 nF
L _i	= 0

10m of cable	
U _i	= 28 V
I _i	= 93 mA
P _i	= 0.65 W
C _i	= 5.0 nF
L _i	= 7.2 μH

92m of cable	
U _i	= 28 V
I _i	= 93 mA
P _i	= 0.65 W
C _i	= 35.9 nF
L _i	= 66 μH

*300 m of cable	
U _i	= 28 V
I _i	= 93 mA
P _i	= 0.65 W
C _i	= 64.2 nF
L _i	= 150 μH

Tri-axial accelerometer

Connector Only	
U _i	= 28 V
I _i	= 93 mA
P _i	= 0.65 W
C _i	= 3.6 nF
L _i	= 0

10m of cable	
U _i	= 28 V
I _i	= 93 mA
P _i	= 0.65 W
C _i	= 7.4 nF
L _i	= 7.2 μH

92m of cable	
U _i	= 28 V
I _i	= 93 mA
P _i	= 0.65 W
C _i	= 38.3 nF
L _i	= 66 μH

*300 m of cable	
U _i	= 28V
I _i	= 93mA
P _i	= 0.65W
C _i	= 66.6 nF
L _i	= 150 μH

Note: The construction of the accelerometers are controlled by the part number. Products with the part numbers HS-150****40**, HS-170****40** and HS-173****40** are the only models that are permitted to have an integral cable length of 300 m where “*” may be any alphanumeric value defined by the applicant. The terminal parameters for a 300 m length of integral cable are only applicable to these part numbers. All other part numbers, where integral cable options are selected, are limited to 92 m under this certification.